

8.9. Common Action Information Blocks and Paths

Shown below are common information blocks used to submit actions to, and receive actions from, the message layer.

8.9.1. Path Information

- Logically for this specification, the Node or Group SHALL be present in all paths.
- When an outgoing path indicates the same Node or Group as the action target, the message layer MAY optimize the path by removing Node or Group.
- When an incoming path does not indicate a Node or Group, the message layer SHALL add the action target (Node or Group) to the path.

See [Path](#) for more information.

8.9.1.1. ClusterPathIB

Path Field	Type	Quality	Conformance
Group	group-id		!Endpoint
Node	node-id		!Group
Endpoint	endpoint-no	A	!Group
Cluster	cluster-id	A	M

8.9.2. Attribute Information Blocks

8.9.2.1. AttributePathIB

An attribute path supports nesting levels deeper than the attribute with the NestedPath field below. The NestedPath indicates zero or more nesting levels to establish the nesting depth of the attribute path.

- An attribute path MAY indicate data at any nesting depth in the attribute data.
- If the Attribute is indicated as a wildcard then the path SHALL indicate all attributes of the cluster.
- If the Attribute is indicated as a wildcard, then NestedPath SHALL be empty.
- If the final nesting level in an attribute path indicates a [collection data type](#), then the path SHALL indicate all collection data, plus any deeper nested data as part of the collection.
- If the WildcardPathFlags field is absent, it SHALL be considered to be an empty map with all flags unset.

Path Field	Type	Quality	Conformance
Cluster	ClusterPathIB		M
Attribute	attrib-id	A	M