

8.9.2.5. WildcardPathFlagsBitmap

This data type is derived from map32.

The WildcardPathFlagsBitmap indicates flags that apply to the path, affecting wildcard expansion.

The following flags are defined:

Bit	Name	Summary
0	WildcardSkipRootNode	Skip the Root Node endpoint (endpoint 0) during wildcard expansion.
1	WildcardSkipGlobalAttributes	Skip several large global attributes during wildcard expansion.
2	WildcardSkipAttributeList	Skip the AttributeList global attribute during wildcard expansion.
3	DoNotUse	
4	WildcardSkipCommandLists	Skip the AcceptedCommandList and GeneratedCommandList global attributes during wildcard expansion.
5	WildcardSkipCustomElements	Skip any manufacturer-specific clusters or attributes during wildcard expansion.
6	WildcardSkipFixedAttributes	Skip any Fixed (F) quality attributes during wildcard expansion.
7	WildcardSkipChangesOmittedAttributes	Skip any Changes Omitted (C) quality attributes during wildcard expansion.
8	WildcardSkipDiagnosticsClusters	Skip all clusters with the Diagnostics (K) quality during wildcard expansion.

8.9.2.6. Valid Read Attribute Paths

This table is valid for [AttributePathIB](#) for a Read Request action or a Subscribe Request action. See [AttributePathIB](#) for more conformance restrictions.

The table defines valid attribute data path with wildcard and non-wildcard combinations.