

Node	Endpoint	Group	Cluster	Command	Description	Conformance
		Specific	Specific	Specific	a specific cluster command to a group of endpoints	M

NOTE Support for commands paths involving wildcards is provisional.

8.9.4.3. CommandDataIB

Info Field	Type	Quality	Conformance
CommandPath	CommandPathIB		M
CommandFields	<i>variable</i>		M
CommandRef	uint16		O

CommandRef field

This field is used to provide a reference for a command.

- When used in an Invoke Request Action:
 - This field MAY be omitted if InvokeRequests contains only a single CommandDataIB.
 - When InvokeRequests contains multiple CommandDataIBs, the CommandRef field SHALL contain a value unique within InvokeRequests.
 - Implementations MAY choose to use the index of the CommandDataIB within the InvokeRequests field as the value of this field.
- When used in an Invoke Response Action:
 - CommandRef MAY be omitted from the CommandDataIB in InvokeResponses if the InvokeRequests being responded to contains only a single CommandDataIB, even if CommandRef was included in that CommandDataIB.
 - CommandRef SHALL be included in the CommandDataIB in InvokeResponses if InvokeRequests contained more than one CommandDataIB.
 - When a CommandDataIB in InvokeResponses has a CommandRef field, its value SHALL be equal to the CommandRef field from the CommandDataIB (in the InvokeRequests) that generated this CommandDataIB.
 - If InvokeRequests contained only a single CommandDataIB, and CommandRef was not included in that CommandDataIB, then CommandRef for this CommandDataIB in InvokeResponses SHALL NOT be included.

8.9.4.4. InvokeResponseIB

This is used in response to an invoked command.