

Status Code	Value	Summary
0x7D	INVALID_SUBSCRIPTION	Subscription ID is not active.
0x7E	UNSUPPORTED_ACCESS NOT_AUTHORIZED	The sender of the action or command does not have authorization or access. NOT_AUTHORIZED is an obsolete name of this error code.
0x7F	UNSUPPORTED_ENDPOINT	The endpoint indicated is unsupported on the node.
0x80	INVALID_ACTION	The action is malformed, has missing fields, or fields with invalid values. Action not carried out.
0x81	UNSUPPORTED_COMMAND UNSUP_COMMAND	The indicated command ID is not supported on the cluster instance. Command not carried out. UNSUP_COMMAND is an obsolete name for this error code.
0x82	<i>reserved</i>	Deprecated: use UNSUPPORTED_COMMAND
0x83	<i>reserved</i>	Deprecated: use UNSUPPORTED_COMMAND
0x84	<i>reserved</i>	Deprecated: use UNSUPPORTED_COMMAND
0x85	INVALID_COMMAND INVALID_FIELD	The cluster command is malformed, has missing fields, or fields with invalid values. Command not carried out. INVALID_FIELD is an obsolete name for this error code.
0x86	UNSUPPORTED_ATTRIBUTE	The indicated attribute ID, field ID or list entry does not exist for an attribute path.