

Status Code	Value	Summary
0x87	CONSTRAINT_ERROR INVALID_VALUE	Out of range error or set to a reserved value. Attribute keeps its old value. Note that an attribute value may be out of range if an attribute is related to another, e.g. with minimum and maximum attributes. See the individual attribute descriptions for specific details. INVALID_VALUE is an obsolete name for this error code.
0x88	UNSUPPORTED_WRITE READ_ONLY	Attempt to write a read-only attribute. READ_ONLY is an obsolete name for this error code.
0x89	RESOURCE_EXHAUSTED INSUFFICIENT_SPACE	An action or operation failed due to insufficient available resources. INSUFFICIENT_SPACE is an obsolete name for this error code.
0x8A	<i>reserved</i>	Legacy cluster specification error status code: use SUCCESS
0x8B	NOT_FOUND	The indicated data field or entry could not be found.
0x8C	UNREPORTABLE_ATTRIBUTE	Reports cannot be issued for this attribute.
0x8D	INVALID_DATA_TYPE	The data type indicated is undefined or invalid for the indicated data field. Command or action not carried out.
0x8E	<i>reserved</i>	Legacy cluster specification error status code: use UNSUPPORTED_ATTRIBUTE.
0x8F	UNSUPPORTED_READ	Attempt to read a write-only attribute.
0x90	<i>reserved</i>	Deprecated: use FAILURE
0x91	<i>reserved</i>	Deprecated: use FAILURE
0x92	DATA_VERSION_MISMATCH	Cluster instance data version did not match request path