

Status Code	Value	Summary
0x93	<i>reserved</i>	Legacy cluster specification error status code: use FAILURE
0x94	TIMEOUT	The transaction was aborted due to time being exceeded.
0x95	<i>reserved</i>	ZCL OTA Upgrade cluster specific error status code
0x96	<i>reserved</i>	ZCL OTA Upgrade cluster specific error status code.
0x97	<i>reserved</i>	ZCL OTA Upgrade cluster specific error status code.
0x98	<i>reserved</i>	ZCL OTA Upgrade cluster specific error status code.
0x99	<i>reserved</i>	ZCL OTA Upgrade cluster specific error status code.
0x9A	<i>reserved</i>	ZCL OTA Upgrade cluster specific error status code.
0x9B	UNSUPPORTED_NODE	The node ID indicated is not supported on the node.
0x9C	BUSY	The receiver is busy processing another action that prevents the execution of the incoming action.
0x9D	ACCESS_RESTRICTED	The access to the action or command by the sender is permitted by the ACL but restricted by the ARL.
0xC0	<i>reserved</i>	Deprecated: use FAILURE
0xC1	<i>reserved</i>	Deprecated: use FAILURE
0xC2	<i>reserved</i>	Deprecated: use FAILURE
0xC3	UNSUPPORTED_CLUSTER	The cluster indicated is not supported on the endpoint.
0xC4	<i>reserved</i>	Deprecated: use SUCCESS
0xC5	NO_UPSTREAM_SUBSCRIPTION	Used by proxies to convey to clients the lack of an upstream subscription to a source.