

Chapter 9. System Model Specification

9.1. Practical Information

9.1.1. Revision History

Revision	Description
1	Initial release of this specification
2	Added usage description for TagList
3	Added description related to Node reconfiguration

9.1.2. Scope and Purpose

This is part of a package of Data Model specifications that are agnostic to underlying layers (encoding, message, network, transport, etc.). Each specification below may be independently maintained. This package, as a whole, SHALL be independently maintained as agnostic and decoupled from lower layers. This package may be referenced by inclusion in a set of protocol stack specifications for a complete vertical standard.

Data Model	Defines first order elements and namespace for endpoints, clusters, attributes, data types, etc.
Interaction Model	Defines interactions, transactions and actions between nodes.
System Model	Defines relationships that are managed between endpoints and clusters.
Cluster Library	Reference library of cluster specifications.
Device Library	Reference library of devices type definitions.

9.1.3. Origin Story

The origin of this section is the [Dotdot Architecture Model](#) and parts of Chapter 2 of the [Zigbee Cluster Library specification](#) that define the data model.

This document defines the specific model used in Matter, which has diverged from Zigbee.

9.1.4. Overview

This specification defines persistent relationships between local and remote instances of data model elements, that support a system of operational communication between such instances. A system is a set of nodes and persistent relationships that automate data flow and control based on local or external stimulus.