

Term	Description
Assert/Asserting	Asserting is the act of one device type causing a condition defined in itself or some other device type to be true.
Asserting device type	A device type asserting a condition defined in itself or another device type is the asserting device type.
Asserted	A condition is asserted when it is caused to be true.

The following are the device types which can have conditions asserted:

Device Type	Description
Root Node	The closest root or root-like endpoint to the asserting device type
Bridged Node	
Self	The device type itself
Child	See Section 9.2, “Endpoint Composition” for the definition of Child

The conditions which can be asserted by an asserting device type are listed in the Condition Requirements table in the definition of the asserting device type. The contents of this table reference conditions defined in the device type itself or in other device types.

The table contains the following columns:

Column	Description
Location	Indicates where this condition is being asserted and is one of Root, Self, or Descendant
Device Type ID	The device type ID of the device where the condition being asserted is defined
Device Type Name	The device type name associated with the device type ID above
Condition	The condition being asserted
Constraint	Any numerical constraints on this condition
Conformance	The conformance for the asserted condition

For example, the Meter Reference Point device type asserts the TimeSyncCond condition as mandatory on the Root Node device type, where it is defined as optional in the Root Node definition. The Meter Reference Point device type is the asserting device type and the TimeSyncCond condition is the asserted condition.

The conformance for a condition MAY contain any valid conformance expression as allowed by this