

mation to the user (e.g. showing it in a user interface), as appropriate.

- A client SHOULD use these tags in its logic to make decisions, as appropriate.

For example, a client MAY identify which endpoint maps to a certain function, orientation or labeling.

A client MAY use the Label field of each [SemanticTagStruct](#), if present in each structure, to indicate characteristics of an endpoint, or to augment what is provided in the TagID field of the same structure.

9.5.6.6. EndpointUniqueID Attribute

This attribute SHALL indicate an identifier which allows to uniquely identify the functionality exposed on an endpoint, and therefore SHALL be unique within the device. It is constructed in a manufacturer specific manner.

- If a globally unique identifier is used, the same [rules](#) as defined for the UniqueID attribute in the Basic Information cluster apply.
- If the identifier is only unique in the scope of the device, and cannot be used to track the device, then it MAY remain unchanged at factory reset.

The value does not need to be human readable, since it is intended for machine to machine (M2M) communication.

9.6. Binding Cluster

NOTE

This scope of this document is the Binding cluster as part of the Cluster Library. The Binding cluster is meant to replace the support from the Zigbee Device Object (ZDO) for supporting the binding table.

A binding represents a persistent relationship between an endpoint and one or more other local or remote endpoints. A binding does not require that the relationship exists. It is up to the node application to set up the relationship.

A binding is used to inform a client endpoint of one or more targets for a potential interaction. For example: a light switch that controls one or more light bulbs, needs to be told the nodes and endpoints of the bulbs, or told a group in which the bulbs are members. For example: A client that needs to subscribe to an occupancy sensor, needs to know the node and endpoint of the sensor.

In such cases, a binding is used to direct a local endpoint to a target. The existence of the Binding cluster on the client endpoint, allows the creation of one or more binding entries (bindings) in the Binding cluster.

Each binding indicates another endpoint or cluster on another endpoint. Multiple bindings are allowed, depending on the interaction.

A binding is either a unicast binding, where the target is a single endpoint on a single node, or a groupcast binding, where the target is a group, which may indicate multiple endpoints on multiple