

9.7.4. Data Types

9.7.4.1. LabelStruct Type

This is a string tuple with strings that are user defined.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	Label	string	max 16		empty		M
1	Value	string	max 16		empty		M

Label Field

The Label or Value semantic is not defined here.

Label examples: "room", "zone", "group", "direction".

Value Field

The Label or Value semantic is not defined here. The Value is a discriminator for a Label that may have multiple instances.

Label:Value examples: "room":"bedroom 2", "orientation":"North", "floor":"2", "direction":"up"

9.7.5. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	LabelList	list[LabelStruct]					M

9.7.5.1. LabelList Attribute

This is a list of string tuples. Each entry is a [LabelStruct](#).

9.8. Fixed Label Cluster

This cluster is derived from the Label cluster and provides a feature for the device to tag an endpoint with zero or more read-only labels.

Examples:

- A bridge can use this to indicate grouping of bridged devices. For example: All bridged devices whose endpoints have an entry in their LabelList "room":"bedroom 2" are in the same (bed)room.
- A manufacturer can use this to identify a characteristic of an endpoint. For example to identify the endpoints of a luminaire, one pointing up, the other pointing down, one of the endpoints would have a LabelList entry "orientation":"up" while the other would have "orienta-