

9.10.5.5. AccessControlTargetStruct Type

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	Cluster	cluster-id	all	X			M
1	Endpoint	endpoint-no	all	X			M
2	Device-Type	devtype-id	all	X			M

9.10.5.6. AccessControlEntryStruct Type

Access Modifier: Fabric Scoped							
ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
1	Privilege	AccessControlEntryPrivilegeEnum	all			S	M
2	AuthMode	AccessControlEntryAuthModeEnum	all			S	M
3	Subjects	list[subject-id]	max SubjectsPerAccessControlEntry	X		S	M
4	Targets	list[AccessControlTargetStruct]	max TargetsPerAccessControlEntry	X		S	M

Privilege Field

The privilege field SHALL specify the level of privilege granted by this Access Control Entry.

Each privilege builds upon its predecessor, expanding the set of actions that can be performed upon a Node. Administer is the highest privilege, and is special as it pertains to the administration of privileges itself, via the Access Control Cluster.

When a Node is granted a particular privilege, it is also implicitly granted all logically lower privilege levels as well. The following diagram illustrates how the higher privilege levels subsume the lower privilege levels: