

AuthMode Field

The AuthMode field SHALL specify the authentication mode required by this Access Control Entry.

Subjects Field

The subjects field SHALL specify a list of [Subject IDs](#), to which this Access Control Entry grants access.

Device types MAY impose additional constraints on the minimum number of subjects per Access Control Entry.

An attempt to create an entry with more subjects than the node can support SHALL result in a RESOURCE_EXHAUSTED error and the entry SHALL NOT be created.

Subject ID SHALL be of type uint64 with semantics depending on the entry’s AuthMode as follows:

Subject Semantics

AuthMode	Subject
PASE	Lower 16-bits → Passcode ID Upper 48-bits → all bits clear
CASE	64-bits → Node ID or CASE Authenticated Tag
Group	Lower 16-bits → Group ID Upper 48-bits → all bits clear

An empty subjects list indicates a wildcard; that is, this entry SHALL grant access to any Node that successfully authenticates via AuthMode. The subjects list SHALL NOT be empty if the entry’s Auth-Mode is PASE.

The PASE AuthMode is reserved for future use (see [Section 6.6.2.9, “Bootstrapping of the Access Control Cluster”](#)). An attempt to write an entry with AuthMode set to PASE SHALL fail with a status code of CONSTRAINT_ERROR.

For PASE authentication, the Passcode ID identifies the required passcode verifier, and SHALL be 0 for the default commissioning passcode.

For CASE authentication, the Subject ID is a distinguished name within the Operational Certificate shared during CASE session establishment, the type of which is [determined by its range](#) to be one of:

- a Node ID, which identifies the required source node directly (by ID)
- a [CASE Authenticated Tag](#), which identifies the required source node indirectly (by tag)

E.g. an ACL entry with CASE AuthMode that grants privileges to Subject IDs [0x0000_0000_1111_1111, 0x0000_0000_2222_2222, 0x0000_0000_3333_3333] (which are Node IDs) will grant access to Nodes with Node ID 0x0000_0000_1111_1111, 0x0000_0000_2222_2222, or 0x0000_0000_3333_3333, but will not grant access to Nodes with