

Cluster	Endpoint	DeviceType	Target
C			Only cluster C on all endpoints
C		D	Only cluster C on any endpoint with Descriptor containing device type D
C	E		Only cluster C on only endpoint E
C	E	D	Invalid

An empty targets list indicates a wildcard: that is, this entry SHALL grant access to all cluster instances on all endpoints on this Node.

E.g. an entry that grants privileges to the Color Light Bulb Device Type will grant privileges to any cluster on any endpoint that contains the Color Light Bulb device type (whether that cluster is in the Color Light Bulb device type or not), and will not grant privileges to any other cluster on any other endpoint.

E.g. an entry that grants privileges to Endpoint 1 will grant privileges to any cluster on Endpoint 1, and will not grant privileges to any other cluster on any other endpoint.

E.g. an entry that grants privileges to the On/Off Cluster on any endpoint will not grant privileges to any other cluster on any endpoint.

E.g. an entry that grants privileges to the On/Off Cluster with Color Light Bulb Device Type will grant privileges to just the On/Off Cluster on any endpoint that contains the Color Light Bulb device type, and will not grant privileges to any other cluster on any other endpoint (including other clusters in the Color Light Bulb device type, or the On/Off cluster on endpoints that do not contain the Color Light Bulb device type).

E.g. an entry that grants privileges to the On/Off Cluster on Endpoint 1 will not grant privileges to any other cluster on Endpoint 1, or to any other cluster (including the On/Off cluster) on any other endpoint.

9.10.5.7. AccessControlExtensionStruct Type

Access Modifier: Fabric Scoped							
ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
1	Data	octstr	max 128			S	M

Data Field

This field MAY be used by manufacturers to store arbitrary [TLV-encoded](#) data related to a fabric's