

9.10.6.6. **TargetsPerAccessControlEntry Attribute**

This attribute SHALL provide the minimum number of [Targets](#) per entry that are supported by this server.

Since reducing this value over time may invalidate ACL entries already written, this value SHALL NOT decrease across time as software updates occur that could impact this value. If this is a concern for a given implementation, it is recommended to only use the minimum value required and avoid reporting a higher value than the required minimum.

9.10.6.7. **AccessControlEntriesPerFabric Attribute**

This attribute SHALL provide the minimum number of [ACL Entries](#) per fabric that are supported by this server.

Since reducing this value over time may invalidate ACL entries already written, this value SHALL NOT decrease across time as software updates occur that could impact this value. If this is a concern for a given implementation, it is recommended to only use the minimum value required and avoid reporting a higher value than the required minimum.

9.10.6.8. **CommissioningARL Attribute**

This attribute SHALL provide the set of [CommissioningAccessRestrictionEntryStruct](#) applied during commissioning on a managed device.

When present, the CommissioningARL attribute SHALL indicate the access restrictions applying during commissioning.

Attempts to access data model elements described by an entry in the CommissioningARL attribute during commissioning SHALL result in an error of ACCESS_RESTRICTED. See [Access Control Model](#) for more information about the features related to controlling access to a Node's Endpoint Clusters ("Targets" hereafter) from other Nodes.

See [Section 9.10.4.2.1, "Managed Device Feature Usage Restrictions"](#) for limitations on the use of access restrictions.

9.10.6.9. **ARL Attribute**

This attribute SHALL provide the set of [AccessRestrictionEntryStruct](#) applied to the associated fabric on a managed device.

When present, the ARL attribute SHALL indicate the access restrictions applying to the accessing fabric. In contrast, the [CommissioningARL](#) attribute indicates the accessing restrictions that apply when there is no accessing fabric, such as during commissioning.

The access restrictions are externally added/removed based on the particular relationship the device hosting this server has with external entities such as its owner, external service provider, or end-user.

Attempts to access data model elements described by an entry in the ARL attribute for the accessing fabric SHALL result in an error of ACCESS_RESTRICTED. See [Access Control Model](#) for more infor-