

AdminNodeID Field

The Node ID of the Administrator that made the change, if the change occurred via a CASE session.

Exactly one of AdminNodeID and AdminPasscodeID SHALL be set, depending on whether the change occurred via a CASE or PASE session; the other SHALL be null.

AdminPasscodeID Field

The Passcode ID of the Administrator that made the change, if the change occurred via a PASE session. Non-zero values are reserved for future use (see [PasscodeId generation in PBKDFParamRequest](#)).

Exactly one of AdminNodeID and AdminPasscodeID SHALL be set, depending on whether the change occurred via a CASE or PASE session; the other SHALL be null.

ChangeType Field

The [type of change](#) as appropriate.

LatestValue Field

The latest value of the changed [extension](#).

This field SHOULD be set if resources are adequate for it; otherwise it SHALL be set to NULL if resources are scarce.

9.10.9.3. FabricRestrictionReviewUpdate Event

The server SHALL generate a FabricRestrictionReviewUpdate event to indicate completion of a fabric restriction review. Due to the requirement to generate this event within a bound time frame of successful receipt of the [ReviewFabricRestrictions](#) command, this event MAY include additional steps that the client MAY present to the user in order to help the user locate the user interface for the Managed Device feature.

Access Modifier: Fabric-Sensitive						
ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Token	uint64	all			M
1	Instruction	string	max 512			O
2	ARLRequest-FlowUrl	string	max 256			O

Token Field

This field SHALL indicate the Token that can be used to correlate a ReviewFabricRestrictionsResponse with a FabricRestrictionReviewUpdate event.