

ment field (if present), SHALL remain as provided by the client through embedding within the **ExpandedARLRequestFlowUrl**, including the order of query key/value pairs present.

### Expansion of CallbackUrl by the manufacturer custom flow

Once the **CallbackUrl** is obtained by the manufacturer flow, it MAY be expanded to form a final **ExpandedARLRequestCallbackUrl** URL to be used by proceeding with the following substitution algorithm on the provided **CallbackUrl**:

- If key **MTaer** is present, the manufacturer custom flow having received the initial query containing the **CallbackUrl** SHALL substitute the placeholder value "\_" (i.e. in **MTaer=**\_ ) in the **CallbackUrl** with the final status of the access extension request flow which SHALL be one of the following. Any value returned in the **MTaer** field not listed above SHALL be considered an error and SHALL be treated as **GeneralFailure**.
  - **Success** - The flow completed successfully and the ARL attribute was updated. The client MAY now read the ARL attribute to determine the new access restrictions.
  - **NoChange** - The ARL attribute was already listing minimum restrictions for the requesting fabric.
  - **GeneralFailure** - The flow failed for an unspecified reason.
  - **FlowAuthFailure** - The user failed to authenticate to the flow.
  - **NotFound** - Access extension failed because the target fabric was not found.

A manufacturer custom flow having received an **ExpandedARLRequestFlowUrl** SHOULD attempt to open the **ExpandedARLRequestCallbackUrl**, on completion of the request, if an **ExpandedARLRequestCallbackUrl** was computed from the **CallbackUrl** and opening such a URL is supported.

### Examples of ARLRequestFlowUrl URLs

Below are some examples of valid **ExpandedARLRequestFlowUrl** for several valid values of **ARLRequestFlowUrl**, as well as some examples of invalid values of **ARLRequestFlowUrl**:

- Invalid URL with no query string: **http** scheme is not allowed:
  - <http://company.domain.example/matter/arl/vFFF1p1234>
- Valid URL :
  - <https://company.domain.example/matter/arl/vFFF1p1234>
- Valid URL, **CallbackUrl** requested:
  - Before expansion:

```
https://company.domain.example/matter/arl?vid=FFF1&pid=1234&MTcu=
```

- After expansion:

```
https://company.domain.example/matter/arl?vid=FFF1&pid=1234&MTcu=https%3A%2F%2Fclient.domain.example%2Fcb%3Ftoken%3DmAsJ6_vqbr-vjDiG_w%253D%253D%26MTaer%3D_
```