

- The **ExpandedARLRequestFlowUrl** URL contains:
 - A **CallbackUrl** with a client-provided arbitrary **token=** key/value pair and the **MTaer=** key/value pair place-holder to indicate support for a return access extension completion status: https://client.domain.example/cb?token=mAsJ6_vqbr-vjDiG_w%3D%3D&MTaer=_
 - After expansion of the **CallbackUrl** (**MTcu** key) into an **ExpandedCallbackUrl**, with an example return access extension completion status of **Success**, the **ExpandedARLRequestCallbackUrl** would be:

```
https://client.domain.example/cb?token=mAsJ6_vqbr-  
vjDiG_w%3D%3D&MTaer=Success
```

Note that the **MTcu** key/value pair was initially provided URL-encoded within the **ExpandedARLRequestFlowUrl** URL and the **MTaer=_** key/value pair placeholder now contains a substituted returned completion status.

- Invalid URL, due to **MTza=79** key/value pair in reserved **MT**-prefixed keys reserved for future use:
 - https://company.domain.example/matter/ar?vid=FFF1&pid=1234&MTop=_&MTza=79

9.11. Group Relationship

A group is a collection of one or more endpoints on one or more nodes. A group is identified by a unique group ID. If the network supports fabrics, each group, its group ID, and nodes that are members of the group, are all scoped to a single fabric.

Conceptually, there is a Group Table on each node that represents endpoint group membership. Each Group Table entry maps a group ID to one or more endpoints on that node, and any endpoint on a node MAY be assigned to one or more groups.

A group relationship, that is contained in the Group Table, is managed through the endpoints using the Groups cluster.

The Interaction Model allows a group identifier to be used as the destination of a message or action. If a message received by a node has a group destination, the Group Table is checked to see which endpoints on the node are members of the group. Then, the message will be delivered to those endpoints.

Note that there is a risk that multiple clients allocate the same group identifier for their own purpose. This likely leads to undesired behavior. For this reason, a client SHOULD discover the uniqueness of their 'candidate' group ID.

Also note that groupcast relies on its support by the underlying network layer. Depending on this network layer, groupcast may not work to "sleepy" devices that have their radio turned off when idle to preserve battery lifetime.