

- a DeviceTypeList attribute containing device type Bridged Node plus the device type(s) of the Bridged Device, and
- a PartsList attribute listing any other endpoints which jointly expose the functionality of this Bridged Device.

Information about power sources for Bridged Devices

In case the Bridged Device contains a power source such as battery or mains power feed, *and* information about the state of that power source is available to the Bridge, the Bridge SHALL also include one or more **Power Source** cluster(s), where their EndpointList attribute SHALL contain the endpoint(s) of the Bridged Device that are powered by this power source. Each endpoint with a Power Source cluster SHALL have the related Power Source device type in its DeviceTypeList.

For Bridged Devices which are represented by a single endpoint:

- The **Power Source** cluster SHALL be included on that single endpoint. An example of this is shown for the battery-powered temperature sensor on endpoint 23 in [Figure 66, “example of endpoints representing Bridged Devices using grouping”](#).

For Bridged Devices which are represented by multiple endpoints:

- If the Bridged Device contains only one power source, the **Power Source** cluster SHALL be present on an endpoint which corresponds to the part of the Bridged Device being powered by the power source.
 - In case this power source provides power to the entire Bridged Device, the power source cluster SHALL be on the endpoint where the Bridged Node device type is located, and contain an EndpointList attribute containing all the endpoints constituting the Bridged Device.

In case a Bridged Device does not contain a power source such as battery or mains power feed, *or* information about the state of that power source is not available to the Bridge, the Bridge SHALL NOT include a **Power Source** cluster on the endpoint(s) representing the Bridged Device.

9.12.2.4. Clusters for Bridged Device functionality (device types)

For each Bridged Device, the Bridge SHALL expose the clusters required for a device of the indicated Matter device type(s).

This allows the Matter Nodes to recognize the device type of the Bridged Device and interact with its clusters in the same manner as with a native Matter Node of that device type.

9.12.2.5. Identify for Bridge and Bridged Devices

If the bridge has a mechanism to identify itself to the user (e.g. blinking LED on the bridge itself), the associated Identify cluster SHOULD be used on the endpoint with the Aggregator device type.

For the identification function of individual bridged devices, the conformance for the associated Identify cluster is determined by the application device types on the endpoint(s) representing the bridged device. For example, in the composed lighting device in [Figure 66, “example of endpoints representing Bridged Devices using grouping”](#), each of the endpoints 25 and 26 would have an identify cluster to allow individual identification of each of those lights.