

if that attribute is supported.

Nodes that wish to be notified of added/removed devices SHOULD monitor changes of the PartsList attributes in the Descriptor cluster on the [root node endpoint](#) and on the endpoint which holds the [Aggregator](#) device type, as well as changes of the ConfigurationVersion attribute in the BasicInformation cluster on the root node endpoint.

Allocation of endpoints for Bridged Devices SHALL be performed as described in [Dynamic Endpoint allocation](#).

9.12.7. Changes to device names and grouping of Bridged Devices

Typically, the user has some means (e.g. a Manufacturer-provided app) to assign names to the Bridged Devices, or names could be assigned automatically by the Bridge. The Bridge SHALL expose such names in the NodeLabel attribute of the Bridged Device Basic Information cluster on the applicable endpoint.

Similarly, the user typically has some means to group the Bridged Devices (e.g. via a room/zone-concept) and provide names to such groups, or grouping could be applied automatically by the Bridge. The Bridge SHOULD expose such grouping using the EndpointLists attribute of the Actions cluster as described above.

For such exposed information, when there is a change in naming/grouping (e.g. the user makes changes via a Manufacturer-provided app), the Bridge SHALL update the appropriate attributes.

Nodes that wish to be notified of a change in such a name or grouping SHOULD monitor changes of this attribute or cluster.

9.12.8. Setup flow for a Bridge (plus Bridged Devices)

As described above, the Bridge together with its Bridged Devices is exposed as a single Node with a list of endpoints. Consequently, a single Node ID and a single Operational Certificate is assigned during Commissioning and a single pass through the commissioning flow is required to bring the Bridge (along with its Bridged Devices) onto a Fabric. This provides for a simple user experience, since the user only needs to go through the commissioning flow for the Bridge, and not separately for each of the Bridged Devices.

9.12.9. Access Control

The Bridge is a Matter node, therefore it has a single [Access Control Cluster](#) for the entire Node, like every other Matter Node. This cluster contains all [Access Control Entries](#) for each of its endpoints, including for all Bridged Devices and other native Matter functionality exposed by the Bridge Node. A typical setup of Access Control would reflect which privilege level a Matter Controller needs to have for one or more Bridged Devices. This overall access set MAY be a subset of all the Bridged Devices on the Bridge, rather than all endpoints on a Bridge. This can be accomplished by setting an Access Control Entry containing as targets a list of those endpoints representing a Bridged Device or a set of Bridged Devices. As defined in [the ACL model](#), it is also possible to specify access towards specific [Targets](#), for example all Bridged Devices of device type [Extended Color Light](#).