

mands to the light when a Scene Recall command is received from a Matter Node.

3. User choice

- A Bridge MAY make it possible (e.g., through a Bridge Manufacturer's app) for its users to further restrict which devices are exposed to the Fabric.

For example, a user may decide to prevent exposure to the Fabric of certain Devices Types, such as all occupancy sensors, or of only certain devices of a certain device type, such as only their bedroom occupancy sensor.

9.12.12. Best practices for Administrators

An Administrator MAY indicate to users which devices are native Matter and which ones are Bridged Devices, as determined using the presence of a **Bridged Node** device type on the endpoint, in order to ensure the user does not make assumptions about the Bridged Devices having the same security requirements as native Matter devices.

9.13. Bridged Device Basic Information Cluster

This cluster provides attributes and events for determining basic information about Bridged Nodes.

This cluster is derived from the Basic Information cluster and serves two purposes towards a Node communicating with a Bridge:

- Indicate that the functionality on the Endpoint where it is placed (and its Parts) is bridged, and
- Provide a centralized collection of attributes that the Node MAY collect to aid in conveying information regarding the Bridged Device to a user, such as the vendor name, the model name, or user-assigned name.

This cluster SHALL be exposed by a Bridge on the Endpoint representing each Bridged Device. When the functionality of a Bridged Device is represented using a set of Endpoints, this cluster SHALL only be exposed on the Endpoint which is at the top of the hierarchy for the functionality of that Bridged Device.

This cluster SHALL NOT be used on an endpoint that is not in the Descriptor cluster PartsList of an endpoint with an Aggregator device type.

This cluster has been derived from the **Basic Information** Cluster, and provides generic information about the Bridged Device. Not all of the attributes in the Basic Information Cluster are relevant for a Bridged Device (e.g. ProductID since it is not a Matter device). For other attributes, the information which is listed as Mandatory for the Basic Information Cluster, may not be available when the Bridged Device does not provide it to the Bridge, and the Bridge has no other means to determine it. For such cases where the information for a particular attribute is not available, the Bridge SHOULD NOT include the attribute in the cluster for this Bridged Device. See below for Conformance details.

9.13.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.