

9.14.5.1. ActionList Attribute

The ActionList attribute holds the list of actions. Each entry SHALL have an unique ActionID, and its EndpointListID SHALL exist in the EndpointLists attribute.

9.14.5.2. EndpointLists Attribute

The EndpointLists attribute holds the list of endpoint lists. Each entry SHALL have an unique EndpointListID.

9.14.5.3. SetupURL Attribute

The SetupURL attribute (when provided) SHALL indicate a URL; its syntax SHALL follow the syntax as specified in [RFC 1738](#), max. 512 ASCII characters and SHALL use the [https](#) scheme. The location referenced by this URL SHALL provide additional information for the actions provided:

- When used without suffix, it SHALL provide information about the various actions which the cluster provides.
 - Example: SetupURL could take the value of `example://Actions` or <https://domain.example/Matter/bridgev1/Actions> for this generic case (access generic info how to use actions provided by this cluster).
- When used with a suffix of `"/?a="` and the decimal value of ActionID for one of the actions, it MAY provide information about that particular action. This could be a deeplink to manufacturer-app/website (associated somehow to the server node) with the information/edit-screen for this action so that the user can view and update details of the action, e.g. edit the scene, or change the wake-up experience time period.
 - Example of SetupURL with suffix added: `example://Actions/?a=12345` or <https://domain.example/Matter/bridgev1/Actions/?a=12345> for linking to specific info/editing of the action with ActionID 0x3039.

9.14.6. Commands

ID	Name	Direction	Response	Access	Conformance
0x00	InstantAction	client ⇒ server	Y	O	desc
0x01	InstantAction- WithTransi- tion	client ⇒ server	Y	O	desc
0x02	StartAction	client ⇒ server	Y	O	desc
0x03	StartAction- WithDuration	client ⇒ server	Y	O	desc
0x04	StopAction	client ⇒ server	Y	O	desc
0x05	PauseAction	client ⇒ server	Y	O	desc
0x06	PauseAction- WithDuration	client ⇒ server	Y	O	desc