

Example: recall a scene on a number of lights.

9.14.6.2. InstantActionWithTransition Command

This command is used to trigger an instantaneous action with a transition over a given time.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	ActionID	uint16	all			M
1	InvokeID	uint32	all			O
2	Transition-Time	uint16	all		MS	M

It is recommended that, where possible (e.g., it is not possible for attributes with Boolean data type), a gradual transition SHOULD take place from the old to the new state over this time period. However, the exact transition is manufacturer dependent.

This command triggers an action (state change) on the involved endpoints, with a specified time to transition from the current state to the new state. During the transition, the action's state SHALL be Active. Afterwards, the action's state SHALL be Inactive.

Example: recall a scene on a number of lights, with a specified transition time.

TransitionTime Field

This field SHALL indicate the transition time in 1/10th of seconds.

9.14.6.3. StartAction Command

This command is used to trigger the commencement of an action.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	ActionID	uint16	all			M
1	InvokeID	uint32	all			O

This command triggers the commencement of an action on the involved endpoints. Afterwards, the action's state SHALL be Active.

Example: start a dynamic lighting pattern (such as gradually rotating the colors around the set-points of the scene) on a set of lights.

Example: start a sequence of events such as a wake-up experience involving lights moving through several brightness/color combinations and the window covering gradually opening.

9.14.6.4. StartActionWithDuration Command

This command is used to trigger the commencement of an action with a duration.