

Uncommissioned State

An ICD is in the *Uncommissioned* state when it has not been provided with any credentials to join a fabric. In this state, the ICD is passively waiting for incoming messages during the [open commissioning window](#).

Unregistered State

An ICD is in the *Unregistered* state with a given [MonitoredSubject](#) when no established relationship with the client exists, meaning the ICD has neither a registration entry in the [ICD Management cluster](#) nor an active subscription associated with the client. In this state, the ICD is passively waiting for incoming messages during its [Active Mode Duration](#).

Check-in State

An ICD is in the *Check-in* state when a registration entry is present for the client in the [ICD Management cluster](#), but no active subscription exists for that client. In this state, the ICD sends Check-In messages instead of subscription reports/events. The Check-In message notifies the client that the ICD is available for communication.

When in the Check-in state, each time an ICD transitions from [Idle Mode](#) to [Active Mode](#), the ICD SHALL attempt to send a Check-In message to each registered ([MonitoredSubject](#)) client that are [resident](#) clients without an active subscription, effectively attempting to send a Check-In message every [Idle Mode Duration](#). The ICD SHOULD NOT attempt to send Check-In messages to clients that have been registered as [ephemeral](#) clients.

The ICD MAY back-off (i.e. skip some of these Check-In messages) when it does not experience interactions from the registered client (e.g. if that client has left the home network) after several consecutive Check-In messages. The time between Check-In messages SHALL NOT be larger than the duration (in seconds) specified in [MaximumCheckInBackoff](#). The number of consecutive missed Check-In messages required to start backing-off is manufacturer specific. The missed Check-In message counters SHALL be reset to 0 for all registered clients when a [user active mode trigger](#) is executed.

Subscribed State

An ICD is in the *Subscribed* state with a given [MonitoredSubject](#) when it has at least one active subscription with the client. It is not necessary to have an entry in the [ICD Management cluster](#) to be in the subscribed state. The ICD MAY be in the subscribed state most of its operating time. In this state, the ICD's goal is to notify the client when it is available for communication with subscription reports.

Message Format

All Check-In messages SHALL be structured as specified in [Message Format](#).

All Check-In messages are unsecured at the message layer:

- The [Session ID](#) field SHALL be set to 0.
- The [Session Type](#) bits of the [Security Flags](#) SHALL be set to 0.
- The [S Flag](#) field of the [Message Flags](#) SHALL be set to 0.