

CheckInNodeID Field

This field SHALL provide the node ID to which a Check-In message will be sent if there are no active subscriptions matching MonitoredSubject.

MonitoredSubject Field

This field SHALL provide the monitored subject ID.

Key Field

This field SHALL contain the ICDToken, a 128-bit symmetric key shared by the ICD and the ICD Client, used to encrypt [Check-In](#) messages from this ICD to the MonitoredSubject.

VerificationKey Field

This field SHALL provide the verification key. The verification key represents the key already stored on the server. The verification key provided in this field SHALL be used by the server to guarantee that a client with manage permissions can only modify entries that contain a Key equal to the verification key. The verification key SHALL be provided for clients with manage permissions. The verification key SHOULD NOT be provided by clients with administrator permissions for the server cluster. The verification key SHALL be ignored by the server if it is provided by a client with administrator permissions for the server cluster.

ClientType Field

This field SHALL provide the client type of the client registering.

Effect on Receipt

On receipt of the RegisterClient command, the server SHALL perform the following procedure:

1. The server verifies that an entry for the fabric is available in the server's list of registered clients.
 - a. If one of the entries in storage for the fabric has the same CheckInNodeID as the received CheckInNodeID, the server SHALL continue from step 2.
 - b. If there is an available entry for the fabric, an entry is created for the fabric and the received CheckInNodeID, MonitoredSubject, Key and ClientType are stored. The server SHALL continue from step 5.
 - c. If there are no available entries for the fabric, the status SHALL be RESOURCE_EXHAUSTED and the server SHALL continue from step 6.
2. The server SHALL verify the privileges of the command's [ISD](#).
 - a. If the [ISD](#) of the command has administrator privileges for the server cluster, the server SHALL continue from step 4.
 - b. If the [ISD](#) of the command does not have administrator privileges for the server cluster, the server SHALL continue from step 3.
3. The server SHALL verify that the received verification key is equal to the key previously stored in the list of registered clients with the matching CheckInNodeID.