

The ICD SHALL report the calculated **PromisedActiveDuration** in a **StayActiveResponse** message back to the client.

9.16.7.5. StayActiveResponse Command

This message SHALL be sent by the ICD in response to the **StayActiveRequest** command and SHALL contain the computed duration (in milliseconds) that the ICD intends to stay active for.

This command SHALL have the following data fields:

| ID | Name                          | Type   | Constraint | Quality | Fallback | Conformance |
|----|-------------------------------|--------|------------|---------|----------|-------------|
| 0  | <b>PromisedActiveDuration</b> | uint32 | desc       |         |          | M           |

PromisedActiveDuration Field

This field SHALL provide the actual duration that the ICD server can stay active from the time it receives the **StayActiveRequest** command.

Minimum Value for PromisedActiveDuration

The minimum value of the **PromisedActiveDuration** field SHALL be equal to either **30000 milliseconds** or **StayActiveDuration** (from the received **StayActiveRequest** command), whichever is smaller.

Example scenarios:

- A Client requests an ICD to stay awake for 20000 milliseconds in its **StayActiveDuration** field. The ICD responds with 20000 in its **PromisedActiveDuration** if it can stay active for that duration.
- A Client requests an ICD to stay awake for 35000 milliseconds in its **StayActiveDuration** field. The ICD responds with 30000 in its **PromisedActiveDuration** since it can only stay active for that minimal amount.
- A Client requests an ICD to stay awake for 10000 milliseconds in its **StayActiveDuration** field, but the ICD’s remaining active time is 20000 milliseconds. The ICD responds with 20000 milliseconds in its **PromisedActiveDuration** field since it intends to stay active that long.

9.17. Ecosystem Information Cluster

The Ecosystem Information Cluster provides extended device information for all the logical devices represented by a Bridged Node. The Ecosystem Information Cluster presents the view of device name and location metadata for presentation by a client of the cluster to a user. This cluster is intended to support Fabric Synchronization and be present on an endpoint with the BridgedNode device type listed in the DeviceTypeList of the endpoint’s Descriptor cluster.