

BridgedEndpoint Field

This field SHALL indicate the endpoint this EcosystemDeviceStruct is associated with on this Bridge.

This field SHALL be present and set to a valid endpoint if the device is accessible through the bridge.

OriginalEndpoint Field

This field SHALL indicate the endpoint this EcosystemDeviceStruct is associated with on the original device represented by this bridge’s Bridged Node. If this bridge is receiving the device from another bridge, then the OriginalEndpoint field value would be the same on both bridges. This field SHALL be present and set to a valid endpoint on the original device if that device is a Matter device.

DeviceTypes Field

This field SHALL indicate all of the DeviceTypes within the DeviceTypeList in the Descriptor Cluster associated with this EcosystemDeviceStruct entry.

This field SHALL contain a list of valid device type ids.

UniqueLocationIDs Field

This field SHALL specify the EcosystemLocationStruct entries in the LocationDirectory attribute associated with this EcosystemDeviceStruct.

UniqueLocationIDsLastEdit Field

This field SHALL indicate the timestamp of when the UniqueLocationIDs was last modified.

NOTE

If multiple server instances update the UniqueLocationIDs field at the same time, it is possible one of the updates will be missed. This is considered an acceptable limitation to reduce the complexity of the design. Since this is meant to be provided from user input, it is unlikely these signals would be happening at one time.

9.17.4.3. EcosystemLocationStruct Type

Access Modifier: Fabric Scoped							
ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	UniqueLocationID	string	max 64			S	M
1	Location-Descriptor	location-desc				S	M
2	Location-DescriptorLastEdit	epoch-us			0	S	M