

# Chapter 10. Interaction Model Encoding Specification

## 10.1. Overview

This specification details the encoding of the [Interaction Model](#) (IM) in the [Matter TLV format](#).

Specifically, it details the encoding of the application payload for Matter messages that map to the Interaction Model. The details of the message header are described in [Section 4.4, “Message Frame Format”](#) and out of scope of this document.

## 10.2. Messages

### 10.2.1. IM Protocol Messages

Each Action in the IM specification SHALL be mapped to a message with a unique [Protocol Opcode](#), namespaced under the [PROTOCOL\\_ID\\_INTERACTION\\_MODEL Protocol ID](#).

- [Vendor ID](#) = 0x0000 (Matter Common)
- [Protocol ID](#) = [PROTOCOL\\_ID\\_INTERACTION\\_MODEL](#)

| Protocol Opcode | Action             | Message                                  |
|-----------------|--------------------|------------------------------------------|
| 0x01            | Status Response    | <a href="#">StatusResponseMessage</a>    |
| 0x02            | Read Request       | <a href="#">ReadRequestMessage</a>       |
| 0x03            | Subscribe Request  | <a href="#">SubscribeRequestMessage</a>  |
| 0x04            | Subscribe Response | <a href="#">SubscribeResponseMessage</a> |
| 0x05            | Report Data        | <a href="#">ReportDataMessage</a>        |
| 0x06            | Write Request      | <a href="#">WriteRequestMessage</a>      |
| 0x07            | Write Response     | <a href="#">WriteResponseMessage</a>     |
| 0x08            | Invoke Request     | <a href="#">InvokeRequestMessage</a>     |
| 0x09            | Invoke Response    | <a href="#">InvokeResponseMessage</a>    |
| 0x0A            | Timed Request      | <a href="#">TimedRequestMessage</a>      |

### 10.2.2. Common Action Information Encoding

Every action SHALL encode the fields specified in [Section 8.2.5.1, “Common Action Information”](#). The methods for encoding Common Action Information fields are:

- As a field in the message header
- As a context tagged field in the action payload

For every field appearing in TLV-encoded data described by the schemas of the following sections,