

**10.4.1.7. Attributes****Spec Writer Note**

*Attributes are supported by the server cluster only.*

| ID     | Name                  | Type                                  | Constraint | Quality | Fallback | Access   | Conformance   |
|--------|-----------------------|---------------------------------------|------------|---------|----------|----------|---------------|
| 0x0000 | <b>Run</b>            | bool                                  | all*       |         | 0        | R V      | M             |
| 0x0001 | <b>Rotate</b>         | <a href="#">RotateEnum</a>            | all        |         | 0        | R V      | M             |
| 0x0002 | <b>Speed</b>          | uint8                                 | 0 to 200*  |         | 0        | R V      | M             |
| 0x0003 | <b>Axis</b>           | uint8                                 | 0 to 90    |         | 0        | RW VO    | AX   WBL      |
| 0x0004 | <b>Wobble-Speed</b>   | uint8                                 | 0 to 200   |         | 0        | RW VO    | WBL           |
| 0x0005 | <b>Patterns</b>       | list[ <a href="#">PatternStruct</a> ] | max 16*    | N*      | 0        | RW VM T* | PAT           |
| 0x0006 | <b>Name</b>           | string                                | max 16     | N       | 0        | RW VM    | P, O          |
| 0x0007 | <b>Wobble-Support</b> | <a href="#">WobbleBitmap</a>          | desc       |         |          | R V      | WobbleSetting |
| 0x0008 | <b>Wobble-Setting</b> | <a href="#">WobbleBitmap</a>          | desc       |         |          | RW VM    | [WBL]         |

**\*Spec Writer Note****Constraint**

- "all" means all possible values.
- "desc" means see attribute description for constraints on attribute.
- "X to Y" means a value range from X=minimum to Y=maximum value.
- "max X" means range or maximum number of entries for a list or bytes for a string type derived from octstr.

**Quality**

- "N" indicates the read only, write only or read & write value is non-volatile across restarts.
- "F" indicates that the read-only value is static (fixed) and will not change in the future (like the ClusterRevision attribute).
- If there is no "N" or "F" then the value is volatile such that the value of the attribute may change at some point in the future.

**Access**

- Access column indicates R=Read Only, RW=Read Write, R\*W=Read [Write], T=Timed Write, View=Read, Operate=Write, Manage=Write, Administer=Write for ACL processing.