

10.4.1.7.8. WobbleSupport Attribute

This attribute SHALL indicate the bits of the [WobbleBitmap](#) supported by the device.

10.4.1.7.9. WobbleSetting Attribute

This attribute SHALL indicate the selected type of wobble. This attribute is constrained to, in case of a write interaction, only accept the bits indicated in the [WobbleSupport](#) attribute.

10.4.1.8. Commands**Spec Writer Note**

Commands are supported by the client & server, but always initiated by the client.

ID	Name	Direction	Response**	Access	Quality	Conformance
0x00	StartRequest	client ⇒ server	Y	O		M
0x01	StopRequest	client ⇒ server	Y	O		M
0x02	ReverseRequest	client ⇒ server	Y	O		REV
0x03	WobbleRequest	client ⇒ server	Y	O		WBL
0x04	PatternRequest	client ⇒ server	Y	M T*		PAT
0x05	StatsRequest	client ⇒ server	StatsResponse**	O		STA
0x06	StatsResponse	client ⇐ server	N	O		STA

***Spec Writer Note**

Commands are operable (O) with Invoke. Commands are operable with Timed (T) Invoke only.

****Spec Writer Note**

"StatsRequest" command has a "StatsResponse" command. "Y" means that the command requires just a status in the Invoke Response. "N" means no response required (most response commands do not need a response).

10.4.1.8.1. StartRequest Command

Upon receipt, this SHALL start the disco ball rotating using the data as follows: