

10.4.1.9.1. Started Event

This event SHALL be generated, when the Run attribute changes from false to true.

10.4.1.9.2. Stopped Event

This event SHALL be generated, when the Run attribute changes from true to false.

10.4.1.9.3. PatternChange Event

This event SHALL be generated when the Rotate, Speed, or WobbleSpeed attributes are written or changed locally as the result of processing the Pattern attribute.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	PrevPattern	Pattern-Struct		X	null	M
1	CurPattern	Pattern-Struct				M
2	NextPattern	Pattern-Struct		X	null	M
3	Label	string	max 32	X	null	O

PrevPattern Field

This field SHALL be the previous pattern run. If there is no previous pattern, then PrevPattern SHALL be null.

CurPattern Field

This field SHALL be the current pattern being run.

NextPattern Field

This field SHALL be the next in the pattern list. If there is no next pattern, the NextPattern event field SHALL be null.

Label Field

This field SHALL indicate additional readable text that describes the reason for the pattern change.

10.4.2. Super Disco Ball Cluster

This is derived* from the Disco Ball cluster, with overrides for qualities and conformance.

*Spec Writer Note

This is an example of a derived cluster, where only stricter conformance overrides, and the Name attribute gets a longer allowed length. If both the Disco Ball and Super Disco Ball