

NOTE

Support for encoding using the EnableTagCompression tag is provisional.

10.6.2.2. Node

- If the **Group** field is present in the **IM representation**, the Group ID is encoded in the **DST** field in the message header and elided from the encoding here.
- The **Node** tag MAY be omitted if the target node of the path matches the NodeID of the server involved in the interaction.

10.6.2.3. Endpoint, Cluster

- Each of these tags can be omitted. The semantics of such omission depend on the value of **EnableTagCompression**.

10.6.2.4. Attribute, ListIndex

- When **EnableTagCompression** is false or not present, they have the following semantics:

Attribute	ListIndex	Description
Omitted	Omitted	Selects all attributes within the specified Node, Endpoint, Cluster
Present	Omitted	Selects a specific attribute within the specified Node, Endpoint, Cluster.
Present	Present	Selects a specific list item within a top-level attribute of type list.

This does not allow expressing all possible paths defined in the interaction model. Only paths that can be expressed MAY be used.

- The **ListIndex** tag is nullable. The null value SHALL only be used when this AttributePathIB is used in an **AttributeDataIB** and indicates a list append operation. See [Section 10.6.4.3.1, “Lists”](#) for more details.

10.6.2.5. Examples

Select all attributes on a given cluster and endpoint:

```
AttributePath = [[ Endpoint = 10, Cluster = Disco Ball ]]
```

Select all attributes in all clusters on a given endpoint:

```
Path = [[ Endpoint = 10 ]]
```