

Select all attributes in all clusters on the node:

```
Path = [[ ]]
```

Select a specific attribute:

```
Path = [[ Endpoint = 10, Cluster = Disco Ball, Attribute = Axis ]]
```

Select a specific item in a top-level list:

```
Path = [[ Endpoint = 10, Cluster = Disco Ball, Attribute = Pattern, ListIndex = 4 ]]
```

Select all attributes in all clusters on a given endpoint on a proxied node:

```
Path = [[ Node = 0x18B430003020203, Endpoint = 10 ]]
```

Tag Compression Example #1:

```
Path1 = [[ Node = 0x18B430003020203, Endpoint = 10, Cluster = Disco Ball, Attribute =
Pattern, ListIndex = 3 ]] // Start tracking path elements.
Path2 = [[ EnableTagCompression = true, ListIndex = 4 ]] // Node, Endpoint, Cluster,
Attribute are re-used from Path1
Path3 = [[ EnableTagCompression = true, ListIndex = 5 ]] // Node, Endpoint, Cluster,
Attribute are re-used from Path1
Path4 = [[ EnableTagCompression = true, Attribute = Axis ]] // Endpoint, Cluster are
re-used from Path1
```

Tag Compression Example #2:

```
Path1 = [[ Node = 0x18B430003020203, Cluster = Disco Ball, Attribute = Pattern,
ListIndex = 3 ]] // Endpoint is wildcard, start tracking path elements.
Path2 = [[ EnableTagCompression = true, ListIndex = 4 ]] // Node, Endpoint (including
wildcard), Cluster, Attribute are re-used from Path1
Path3 = [[ EnableTagCompression = true, ListIndex = 5 ]] // Node, Endpoint (including
wildcard), Cluster, Attribute are re-used from Path1
```

Tag Compression Example #3:

```
Path1 = [[ Node = 0x18B430003020203, Endpoint = 10, Cluster = Disco Ball, Attribute =
Pattern, ListIndex = 3 ]] // Start tracking path elements.
Path2 = [[ EnableTagCompression = true, ListIndex = 4 ]] // Node, Endpoint, Cluster,
Attribute are re-used from Path1
Path3 = [[ EnableTagCompression = true, ListIndex = 5 ]] // Node, Endpoint, Cluster,
```