

```

AttributeDataIB = {
    DataVersion = 1,
    Path = [[ Endpoint = 10, Cluster = Disco Ball, FieldID = Pattern]],
    Data = [[
        {
            Duration = 900,
            Rotate = Clockwise, // On the wire enum value (1) is used
            Speed = 12,
            Axis = 0,
            // WobbleSpeed omitted; this cluster instance does not support Wobble
            Passcode = "1234"
        }
        {
            Duration = 100,
            Rotate = Counterclockwise, // On the wire enum value (2) is used
            Speed = 12,
            Axis = 90,
            // WobbleSpeed omitted; this cluster instance does not support Wobble
            Passcode = "9876"
        }
    ]],
}

```

Replace a list (Multiple IBs):

```

AttributeDataIB1 = {
    DataVersion = 1,
    Path = [[ Endpoint = 10, Cluster = Disco Ball, FieldID = Pattern ]],
    Data = [
    ]
}

AttributeDataIB2 = {
    DataVersion = 1,
    Path = [[ Endpoint = 10, Cluster = Disco Ball, FieldID = Pattern, ListIndex =
null]],
    Data = {
        Duration = 900,
        Rotate = Clockwise, // On the wire enum value (1) is used
        Speed = 12,
        Axis = 0,
        // WobbleSpeed omitted; this cluster instance does not support Wobble
    }
}

```