

10.6.8. EventPathIB

TLV Type: List					
Element	Comments	Tag Type	Tag Number	TLV Type	Range
Node		Context Tag	0	Unsigned Int	64 bits
Endpoint		Context Tag	1	Unsigned Int	16 bits
Cluster		Context Tag	2	Unsigned Int	32 bits
Event		Context Tag	3	Unsigned Int	32 bits
'IsUrgent'		Context Tag	4	Boolean	-

- The contents of [ClusterPathIB](#) have been expanded here to increase encoding efficiency.
- The **Node** tag MAY be omitted if the target node of the path matches the NodeID of the server involved in the interaction.
- Omission of the **Endpoint**, **Cluster** and **Event** tags SHALL have different interpretations depending on where the EventPathIB is used. See [Section 10.7.2.2, “EventRequests”](#), [Section 10.7.4.1, “EventRequests”](#), and [Section 10.7.3.1, “EventReports”](#) for the different contexts.

10.6.8.1. Examples

Select a particular event type:

```
Path = [[ Endpoint = 10, Cluster = Disco Ball, Event = Pattern Change ]]
```

Select all events on a given cluster (used in Read/Subscribe requests):

```
Path = [[ Endpoint = 10, Cluster = Disco Ball ]]
```

Select all events on a given cluster with urgency (used in Read/Subscribe requests):

```
Path = [[ Endpoint = 10, Cluster = Disco Ball, IsUrgent = true ]]
```

10.6.9. EventDataIB

TLV Type: Structure					
Element	Comments	Tag Type	Tag Number	Type	Range
Path		Context Tag	0	EventPathIB	-
EventNumber		Context Tag	1	Unsigned Int	64 bits
Priority		Context Tag	2	Unsigned Int	8 bits
one-of {					