

```
    EventNumber = 1001,
    Priority = INFO,
    EpochTimestamp = 102340234293,
    Data = {
        // Started event contains no data
    }
}
```

10.6.10. EventReportIB

TLV Type: Structure (Anonymous)					
Element	Comments	Tag Type	Tag Number	TLV Type	Range
EventStatus		Context Tag	0	EventStatusIB	-
EventData		Context Tag	1	EventDataIB	-

10.6.11. CommandPathIB

TLV Type: List					
Element	Comments	Tag Type	Tag Number	TLV Type	Range
Endpoint		Context Tag	0	Unsigned Int	16 bits
Cluster		Context Tag	1	Unsigned Int	32 bits
Command		Context Tag	2	Unsigned Int	32 bits

- The contents of ClusterPathIB have been expanded into the CommandPathIB here to increase encoding efficiency.
- Wildcarding is achieved by omission of the respective tag.
- The Node field in the IM representation is the NodeID of the server involved in the interaction. This is omitted in the encoding here since it is retrievable from the message layer for the message containing this element.
- The Group field in the IM representation is encoded in the DST field in the message header.

10.6.11.1. Examples

Select a particular command:

```
Path = [[ Endpoint = 10, Cluster = Disco Ball, Command = Stop Request ]]
```

Select a particular command (addressed to a group):

```
Path = [[ Cluster = Disco Ball, Command = Stop Request ]]
```