

10.7.3.1. EventReports

A list of [EventReportIB](#) encoded as a TLV array that have certain compression schemes applied to them to reduce redundant data.

For each EventReportIB in the list:

- The Path tag SHALL utilize the same [tag compression scheme](#) as that utilized by the tags in [AttributePathIB](#). Specifically:
 - The tag compression scheme SHALL only apply to the **Node**, **Endpoint**, **Cluster** and **Event** tags within the [EventPathIB](#) element.
 - The first element within the list SHALL specify all the necessary tags and hence serve as the anchor on which subsequent items MAY rely for compression.
- The EventNumber MAY be omitted if it is exactly one greater than the EventNumber of the previous Event.
- The 'Delta' tags SHALL be used to encode timestamps as deltas from the prior event to improve compression of large timestamps.

NOTE | Support for using the tag compression scheme for the Path is provisional.

10.7.3.1.1. Examples

Event list (highlighting compressions):

```
EventReports = [  
  {  
    Path = [[ Endpoint = 10, Cluster = Disco Ball, EventID = Started ]],  
    ImportanceLevel = INFO,  
    Number = 1001,  
    UTCTimestamp = 102340234293,  
    Data = {  
    }  
  },  
  {  
    Path = [[ EventID = PatternChange]], // same endpoint and cluster but different  
    event type  
    DeltaUTCTimestamp = 1000,  
    Data = {  
      PrevPattern = null,  
      CurPattern = {  
        Duration = 900,  
        Rotate = Clockwise, // On the wire enum value (1) is used  
        Speed = 12,  
        Axis = 0,  

```