

TLV Type: Structure (Anonymous)					
Element	Comments	Tag Type	Tag Number	Type	Range
KeepSubscriptions		Context Tag	0	Boolean	
MinIntervalFloor		Context Tag	1	Unsigned Int	16 bits
MaxIntervalCeiling		Context Tag	2	Unsigned Int	16 bits
AttributeRequests	Optional	Context Tag	3	Array of AttributePathIB	-
EventRequests	Optional	Context Tag	4	Array of EventPathIB	-
EventFilters	Optional. Only present if EventRequests is present.	Context Tag	5	Array of EventFilterIB	-
FabricFiltered		Context Tag	7	boolean	-
DataVersionFilters	Optional. Only present if AttributeRequests is present.	Context Tag	8	Array of DataVersionFilterIB	-

10.7.4.1. EventRequests

- Omission of any of [Endpoint](#), [Cluster](#), [Event](#) tags indicates wildcard semantics.

10.7.5. SubscribeResponseMessage

This is sent after all Reports have been sent back to the client. The sole purpose of this is to convey the final set of parameters for the subscription back to the client.

TLV Type: Structure (Anonymous)					
Element	Comments	Tag Type	Tag Number	Type	Range
SubscriptionID		Context Tag	0	Unsigned Int	32 bits
MaxInterval		Context Tag	2	Unsigned Int	16 bits

10.7.6. WriteRequestMessage

TLV Type: Structure (Anonymous)					
Element	Comments	Tag Type	Tag Number	Type	Range
SuppressResponse	Omit if 'false'	Context Tag	0	Boolean	-