

TLV Type: Structure (Anonymous)

TimedRequest		Context Tag	1	Boolean	-
WriteRequests		Context Tag	2	Array of AttributeDataIB	
MoreChunkedMessages	Can be omitted if false	Context Tag	3	Boolean	-

10.7.6.1. SuppressResponse

- If **MoreChunkedMessages** is true, **SuppressResponse** SHALL be false.
- If **MoreChunkedMessages** is false, **SuppressResponse** SHALL be set to the SuppressResponse value in the Write Request action being encoded.

10.7.6.2. MoreChunkedMessages

- Multiple WriteRequestMessages SHALL be sent in a single transaction if the set of AttributeDataIBs have to be sent across multiple packets. All but the last message SHALL have the **MoreChunkedMessages** flag set to true to indicate this situation. Before sending the next WriteRequestMessage, the sender SHALL await the WriteResponseMessage associated with the previous WriteRequestMessage.
- A Write Request action that is part of a Timed Write Interaction SHALL NOT be chunked.

10.7.7. WriteResponseMessage

TLV Type: Structure (Anonymous)					
Element	Comments	Tag Type	Tag Number	Type	Range
WriteResponses		Context Tag	0	Array of AttributeStatusIB	-

10.7.8. TimedRequestMessage

TLV Type: Structure (Anonymous)					
Element	Comments	Tag Type	Tag Number	Type	Range
Timeout		Context Tag	0	Unsigned Int	16 bits

10.7.9. InvokeRequestMessage

TLV Type: Structure (Anonymous)					
Element	Comments	Tag Type	Tag Number	Type	Range
SuppressResponse		Context Tag	0	Boolean	-
TimedRequest		Context Tag	1	Boolean	-