

tion of a future boot or reboot process.

11.1.6.3. Leave Event

The Leave event SHOULD be generated by a Node prior to permanently leaving a given Fabric, such as when the [RemoveFabric](#) command is invoked for a given fabric, or triggered by factory reset or some other manufacturer specific action to disable or reset the operational data in the Node. When a Leave event is generated, it SHOULD be assumed that the fabric recorded in the event is no longer usable, and subsequent interactions targeting that fabric will most likely fail.

Upon receipt of Leave Event on a subscription, the receiving Node MAY update other nodes in the fabric by removing related bindings, access control list entries and other data referencing the leaving Node.

The data of this event SHALL contain the following information:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	FabricIndex	fabric-idx	1 to 254			M

FabricIndex Field

This field SHALL contain the local [fabric-index](#) of the fabric which the node is about to leave.

11.1.6.4. ReachableChanged Event

This event (when supported) SHALL be generated when there is a change in the Reachable attribute.

Its main use case is in the derived [Bridged Device Basic Information](#) cluster.

The data of this event SHALL contain the following information:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Reachable-NewValue	bool				M

ReachableNewValue Field

This field SHALL indicate the value of the [Reachable](#) attribute after it was changed.

11.2. Group Key Management Cluster

The Group Key Management cluster manages group keys for the node. The cluster is scoped to the node and is a singleton for the node. This cluster maintains a list of groups supported by the node. Each group list entry supports a single group, with a single group ID and single group key. Duplicate groups are not allowed in the list. Additions or removal of a group entry are performed via modifications of the list. Such modifications require Administer privilege.

Each group entry includes a membership list of zero or more endpoints that are members of the