

Access Modifier: Fabric Scoped							
ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	GroupKey-SetID	uint16	all				M
1	GroupKey-Security-Policy	GroupKey-Security-PolicyEnum	all				M
2	EpochKey0	octstr	16	X			M
3	EpochStartTime0	epoch-us	all	X			M
4	EpochKey1	octstr	16	X			M
5	EpochStartTime1	epoch-us	all	X			M
6	EpochKey2	octstr	16	X			M
7	EpochStartTime2	epoch-us	all	X			M
8	GroupKey-Multicast-Policy	GroupKey-Multicast-PolicyEnum	all				P, M

GroupKeySetID Field

This field SHALL provide the fabric-unique index for the associated group key set, as specified in [Section 4.17.3.5.1, “Group Key Set ID”](#).

GroupKeySecurityPolicy Field

This field SHALL provide the security policy for an operational group key set.

When CacheAndSync is not supported in the [FeatureMap](#) of this cluster, any action attempting to set CacheAndSync in the GroupKeySecurityPolicy field SHALL fail with an INVALID_COMMAND error.

EpochKey0 Field

This field, if not null, SHALL be the root credential used in the derivation of an operational group key for epoch slot 0 of the given group key set. If EpochKey0 is not null, EpochStartTime0 SHALL NOT be null.