

The content of this attribute reflects data managed via the Groups cluster (see [AppClusters](#)), and is in general terms referred to as the 'node-wide Group Table'.

The GroupTable SHALL NOT contain any entry whose [GroupInfoMapStruct](#) has an empty Endpoints list. If a RemoveGroup or RemoveAllGroups command causes the removal of a group mapping from its last mapped endpoint, the entire GroupTable entry for that given GroupId SHALL be removed.

11.2.6.3. MaxGroupsPerFabric Attribute

This attribute SHALL indicate the maximum number of groups that this node supports per fabric. The value of this attribute SHALL be set to be no less than the required minimum supported groups as specified in [Section 2.11.1.2, “Group Limits”](#). The length of the [GroupKeyMap](#) and [GroupTable](#) list attributes SHALL NOT exceed the value of the MaxGroupsPerFabric attribute multiplied by the number of [supported fabrics](#).

11.2.6.4. MaxGroupKeysPerFabric Attribute

This attribute SHALL indicate the maximum number of [group key sets](#) this node supports per fabric. The value of this attribute SHALL be set according to the minimum number of group key sets to support as specified in [Section 2.11.1.2, “Group Limits”](#).

11.2.7. Commands

All commands in this cluster SHALL be [scoped](#) to the accessing fabric.

ID	Name	Direction	Response	Access	Conformance
0x00	KeySetWrite	client ⇒ server	Y	A F	M
0x01	KeySetRead	client ⇒ server	KeySetRead-Response	A F	M
0x02	KeySetRead-Response	client ⇐ server	N		M
0x03	KeySetRemove	client ⇒ server	Y	A F	M
0x04	KeySetReadAllIndices	client ⇒ server	KeySetReadAllIndicesResponse	A F	M
0x05	KeySetReadAllIndicesResponse	client ⇐ server	N		M

11.2.7.1. KeySetWrite Command

This command is used by Administrators to set the state of a given Group Key Set, including atomically updating the state of all epoch keys.