

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	GroupKey-Set	GroupKey-SetStruct				M

Effect on Receipt

The following validations SHALL be done against the content of the GroupKeySet field:

- If the EpochKey0 field is null or its associated EpochStartTime0 field is null, then this command SHALL fail with an INVALID_COMMAND status code responded to the client.
- If the EpochKey0 field's length is not exactly 16 bytes, then this command SHALL fail with a CONSTRAINT_ERROR status code responded to the client.
- If the EpochStartTime0 is set to 0, then this command SHALL fail with an INVALID_COMMAND status code responded to the client. Note that internally, a GroupKeySetStruct's EpochStartTime0 MAY be set to zero, due to the behavior of the AddNOC command which synthesizes a GroupKeySetStruct (see [Section 11.18.6.8.1, "IPKValue Field"](#)). However, the value 0 is illegal in the GroupKeySet field sent by a client.
- If the EpochKey1 field is not null, then the EpochKey0 field SHALL NOT be null. Otherwise this command SHALL fail with an INVALID_COMMAND status code responded to the client.
- If the EpochKey1 field is not null, and the field's length is not exactly 16 bytes, then this command SHALL fail with a CONSTRAINT_ERROR status code responded to the client.
- If the EpochKey1 field is not null, its associated EpochStartTime1 field SHALL NOT be null and SHALL contain a later epoch start time than the epoch start time found in the EpochStartTime0 field. Otherwise this command SHALL fail with an INVALID_COMMAND status code responded to the client.
- If exactly one of the EpochKey1 or EpochStartTime1 is null, rather than both being null, or neither being null, then this command SHALL fail with an INVALID_COMMAND status code responded to the client.
- If the EpochKey2 field is not null, then the EpochKey1 and EpochKey0 fields SHALL NOT be null. Otherwise this command SHALL fail with an INVALID_COMMAND status code responded to the client.
- If the EpochKey2 field is not null, and the field's length is not exactly 16 bytes, then this command SHALL fail with a CONSTRAINT_ERROR status code responded to the client.
- If the EpochKey2 field is not null, its associated EpochStartTime2 field SHALL NOT be null and SHALL contain a later epoch start time than the epoch start time found in the EpochStartTime1 field. Otherwise this command SHALL fail with an INVALID_COMMAND status code responded to the client.
- If exactly one of the EpochKey2 or EpochStartTime2 is null, rather than both being null, or neither being null, then this command SHALL fail with an INVALID_COMMAND status code responded to the client.

If there exists a Group Key Set associated with the accessing fabric which has the same GroupKeySetID as that provided in the GroupKeySet field, then the contents of that group key set SHALL be