

replaced. A replacement SHALL be done by executing the equivalent of entirely removing the previous Group Key Set with the given GroupKeySetID, followed by an addition of a Group Key Set with the provided configuration. Otherwise, if the GroupKeySetID did not match an existing entry, a new Group Key Set associated with the accessing fabric SHALL be created with the provided data. The Group Key Set SHALL be written to non-volatile storage.

Upon completion, this command SHALL send a status code back to the initiator:

- If the Group Key Set was properly installed or updated on the Node, the status code SHALL be set to SUCCESS.
- If there are insufficient resources on the receiver to store an additional Group Key Set, the status code SHALL be set to RESOURCE_EXHAUSTED (see [Section 2.11.1.2, “Group Limits”](#));
- Otherwise, this status code SHALL be set to FAILURE.

11.2.7.2. KeySetRead Command

This command is used by Administrators to read the state of a given Group Key Set.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	GroupKey-SetID	uint16	all			M

Effect on Receipt

If there exists a Group Key Set associated with the accessing fabric which has the same GroupKeySetID as that provided in the GroupKeySetID field, then the contents of that Group Key Set SHALL be sent in a [KeySetReadResponse](#) command, but with the EpochKey0, EpochKey1 and EpochKey2 fields replaced by null.

Otherwise, if the GroupKeySetID does not refer to a Group Key Set associated with the accessing fabric, then this command SHALL fail with a NOT_FOUND status code.

11.2.7.3. KeySetReadResponse Command

This command SHALL be generated in response to the [KeySetRead](#) command, if a valid Group Key Set was found. It SHALL contain the configuration of the requested Group Key Set, with the EpochKey0, EpochKey1 and EpochKey2 key contents replaced by null.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	GroupKey-Set	GroupKey-SetStruct				M

11.2.7.4. KeySetRemove Command

This command is used by Administrators to remove all state of a given Group Key Set.