

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	GroupKey-SetID	uint16	all			M

Effect on Receipt

If there exists a Group Key Set associated with the accessing fabric which has the same GroupKey-SetID as that provided in the GroupKeySetID field, then the contents of that Group Key Set SHALL be removed, including all epoch keys it contains.

If there exist any entries for the accessing fabric within the [GroupKeyMap](#) attribute that refer to the GroupKeySetID just removed, then these entries SHALL be removed from that list.

This command SHALL fail with an INVALID_COMMAND status code back to the initiator if the GroupKeySetID being removed is 0, which is the Key Set associated with the [Identity Protection Key \(IPK\)](#). The only method to remove the IPK is usage of the [RemoveFabric command](#) or any operation which causes the equivalent of a RemoveFabric to occur by side-effect.

This command SHALL send a SUCCESS status code back to the initiator on success, or NOT_FOUND if the GroupKeySetID requested did not exist.

11.2.7.5. KeySetReadAllIndices Command

This command is used by Administrators to query a list of all Group Key Sets associated with the accessing fabric.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	DoNotUse					X

Effect on Receipt

Upon receipt, this command SHALL iterate all stored GroupKeySetStruct associated with the accessing fabric and generate a [KeySetReadAllIndicesResponse](#) command containing the list of GroupKey-SetID values from those structs.

11.2.7.6. KeySetReadAllIndicesResponse Command

This command SHALL be generated in response to [KeySetReadAllIndices](#) and it SHALL contain the list of [GroupKeySetID](#) for all Group Key Sets associated with the scoped Fabric.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	GroupKey-SetIDs	list[uint16]				M