

Value	Name	Summary	Conformance
8	Japanese	Dates conveyed using the Japanese calendar	O.a+
9	Korean	Dates conveyed using the Korean calendar	O.a+
10	Persian	Dates conveyed using the Persian calendar	O.a+
11	Taiwanese	Dates conveyed using the Taiwanese calendar	O.a+
255	UseActiveLocale	calendar implied from active locale	O.a+

11.4.6. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	HourFormat	HourFormatEnum	all	N		RW VM	M
0x0001	ActiveCalendarType	CalendarTypeEnum	all	N		RW VM	CALFMT
0x0002	SupportedCalendarTypes	list[CalendarTypeEnum]	desc	F	N/A	R V	CALFMT

11.4.6.1. HourFormat Attribute

This attribute SHALL represent the format that the Node is currently configured to use when conveying the hour unit of time.

If not UseActiveLocale, this value SHALL take priority over any unit implied through the [ActiveLocale](#) attribute.

If UseActiveLocale, any unit implied through the [ActiveLocale](#) attribute is used as the hour format, and if [ActiveLocale](#) is not present, the hour format is unknown.

11.4.6.2. ActiveCalendarType Attribute

This attribute SHALL represent the calendar format that the Node is currently configured to use when conveying dates.

If not UseActiveLocale, this value SHALL take priority over any unit implied through the [ActiveLocale](#) attribute.

If UseActiveLocale, any unit implied through the [ActiveLocale](#) attribute is used as the calendar type, and if [ActiveLocale](#) is not present, the calendar type is unknown.