

11.6. Power Source Configuration Cluster

This cluster is used to describe the configuration and capabilities of a Device's power system. It provides an ordering overview as well as linking to the one or more endpoints each supporting a Power Source cluster.

11.6.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial revision

11.6.2. Classification

Hierarchy	Role	Scope	PICS Code
Base	Utility	Node	PSCFG

11.6.3. Cluster ID

ID	Name
0x002E	Power Source Configuration

11.6.4. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	Sources	list[end-point-no]	max 6	N		R V	M

11.6.4.1. Sources Attribute

This list SHALL contain the set of all power sources capable of participating in the power system of this Node. Each entry in the list SHALL be the endpoint number of an endpoint having a Power Source cluster, which corresponds to a physical power source. The endpoint number SHALL be unique within the list.

The order of power sources on a Node is defined by the [Order](#) attribute of its associated Power Source cluster provided on the endpoint. List entries SHALL be sorted in increasing order, that is, an entry with a lower order SHALL have a lower index than any entry with a higher order. Multiple entries MAY have the same order, there are no restrictions on their relative sorting.