

Label Field

This field SHALL indicate a friendly name for the node, to be used when the client does not have access to the node's fabric.

11.8.6. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	AvailableEndpoints	list[end-point-no]	max 20	F		R V	SET
0x0001	ActiveEndpoints	list[end-point-no]	max 20	N		R V	DYPF

11.8.6.1. AvailableEndpoints Attribute

This attribute SHALL indicate the list of endpoints capable of providing power to and/or consuming power from the endpoint hosting this server.

11.8.6.2. ActiveEndpoints Attribute

This attribute SHALL indicate the current list of endpoints currently providing or consuming power to or from the endpoint hosting this server. This list SHALL be a subset of the value of the [AvailableEndpoints](#) attribute.

11.8.6.3. ElectricalCircuitNodes Attribute

This attribute SHALL indicate a list of nodes for devices which are on the electrical circuit represented by this server.

11.9. Network Commissioning Cluster

Network commissioning is part of the overall Node commissioning. The main goal of Network Commissioning Cluster is to associate a Node with or manage a Node's one or more network interfaces. These network interfaces can include the following types.

- Wi-Fi ([IEEE 802.11-2020](#))
- Ethernet (802.3)
- Thread (802.15.4)

An instance of the Network Commissioning Cluster only applies to a single network interface instance present. An interface, in this context, is a unique entity that can have an IPv6 address assigned to it and ingress and egress IP packets.