

For Wi-Fi-supporting servers (**WI** feature) the server SHALL always honor directed scans, and attempt to provide all matching BSSID which are reachable on the bands which would otherwise be attempted if a ConnectNetwork having the specified SSID were to take place. This command is useful for clients to determine reachability capabilities as seen by the server's own radios.

For Wi-Fi-supporting servers the server SHALL always scan on all bands supported by the interface associated with the cluster instance on which the command was invoked.

If the command was invoked over the same link whose configuration is managed by a given server cluster instance, there MAY be an impact on other communication from the invoking client, as well as other clients, while the network interface is processing the scan. Clients SHOULD NOT use this command unless actively in the process of re-configuring network connectivity.

The arguments for this command are as follows:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	SSID	octstr	1 to 32	X	null	[WI]
1	Breadcrumb	uint64	all			O

SSID Field

This field, if present, SHALL contain the SSID for a directed scan of that particular Wi-Fi SSID. Otherwise, if the field is absent, or if it is null, this SHALL indicate scanning of all BSSID in range. This field SHALL be ignored for ScanNetworks invocations on non-Wi-Fi server instances.

Breadcrumb Field

The Breadcrumb field, if present, SHALL be used to atomically set the [Breadcrumb](#) attribute in the General Commissioning cluster on success of the associated command. If the command fails, the [Breadcrumb](#) attribute in the General Commissioning cluster SHALL be left unchanged.

11.9.7.2. ScanNetworksResponse Command

This command is used to report the results of a ScanNetworks command.

This command SHALL contain the status of the last ScanNetworks command, and the associated scan results if the operation was successful.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Network- ingStatus	Network- Commission- ingSta- tusEnum	desc			M
1	DebugText	string	max 512			O