

ID	Name	Type	Constraint	Quality	Fallback	Conformance
2	WiFiScan-Results	list[WiFiInterfaceScanResultStruct]	desc			WI
3	Thread-ScanResults	list[ThreadInterfaceScanResultStruct]	desc			TH

Results are valid only if NetworkingStatus is Success.

Before generating a ScanNetworksResponse, the server SHALL set the [LastNetworkingStatus](#) attribute value to the NetworkingStatus matching the response.

NetworkingStatus Field

The NetworkingStatus field SHALL indicate the status of the last scan operation, taking one of these values:

- Success: Scanning succeeded.
- [NetworkNotFound](#): No instance of an explicitly-provided network identifier was found during the scan. This error cannot occur if no network identifier was provided, such as when scanning for all available networks.
- [OutOfRange](#): Network identifier was invalid (e.g. empty, too long, etc).
- [RegulatoryError](#): Could not scan on any bands due to lack of regulatory configuration.
- [UnknownError](#): An internal error occurred during scanning.

DebugText Field

This field, if present and non-empty, MAY contain error information which MAY be communicated to the user in case the NetworkingStatus was not Success. Its purpose is to help developers in troubleshooting errors and MAY go into logs or crash reports.

WiFiScanResults Field

If NetworkingStatus was Success, this field SHALL contain the Wi-Fi network scan results. The list MAY be empty if none were found in range on the bands supported by the interface, or if directed scanning had been used and the desired SSID was not found in range.

The maximum number of results present in the result list supported MAY depend on memory and MAY contain a subset of possibilities, to avoid memory exhaustion on the cluster server and avoid crossing the maximum command response size supported (see [Section 4.4.4, “Message Size Requirements”](#)).

The order in which results are reported is implementation-specific. Results SHOULD be reported in decreasing RSSI order, even if RSSI is not reported in the response, to maximize the likelihood that most likely to be reachable elements are included within the size limits of the response.