

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Operational-Dataset	octstr	max 254			M
1	Breadcrumb	uint64	all			O

The XPAN ID in the OperationalDataset serves as the NetworkID for the network configuration to be added or updated.

If the [Networks](#) attribute does not contain an entry with the same NetworkID as the one provided in the OperationalDataset, the operation SHALL be considered an addition, otherwise, it SHALL be considered an update.

OperationalDataset Field

The OperationalDataset field SHALL contain the Thread Network Parameters, including channel, PAN ID, and Extended PAN ID.

The encoding for the OperationalDataset field is defined in the [Thread specification](#).

The client SHALL pass the OperationalDataset as an opaque octet string.

Breadcrumb Field

See [Section 11.9.7.1.2, “Breadcrumb Field”](#) for usage.

11.9.7.5. Common processing of AddOrUpdateWiFiNetwork and AddOrUpdateThreadNetwork

Both AddOrUpdateWiFiNetwork and AddOrUpdateThreadNetwork operate similarly, against different underlying technologies. The processing of these commands in the addition and update case is covered by the following subsections.

Processing an addition

If the [Networks](#) attribute is already full, the command SHALL immediately respond with NetworkConfigResponse having NetworkingStatus status field set to BoundsExceeded.

If any of the parameters in the OperationalDataset are invalid, the command SHALL immediately respond with NetworkConfigResponse having NetworkingStatus status field set to a value different than Success and consistent with the error.

If validation of all parameters has succeeded, this command SHALL append the configuration at the end of the existing list in the [Networks](#) attribute, making this new network the one with least priority.

On success, the NetworkConfigResponse command SHALL have its NetworkIndex field set to the 0-based index of the entry in the [Networks](#) attribute that was just added.